


Strojní závitník HSS-E

TC115 Perform mm




– Pro materiály s dlouhou třískou



	P	M	K	N	S	H	O
WY80AA	●	●	●	●	●	●	●
WY80FC	●	●	●	●	●	●	●


DIN 371



Označení WY80AA	Označení WY80FC	DN	P mm	l ₁ mm	L _c mm	l ₃ mm	d ₁ h9 mm	□	l ₉ mm	N
TC115-M1.6-C0-	TC115-M1.6-C0-	M 1.6	0,35	40	6	6	2,5	2,1	5	2
TC115-M2-C0-	TC115-M2-C0-	M 2	0,4	45	4	9	2,8	2,1	5	3
TC115-M2.5-C0-	TC115-M2.5-C0-	M 2.5	0,45	50	4	12,5	2,8	2,1	5	3
TC115-M3-C0-	TC115-M3-C0-	M 3	0,5	56	6	18	3,5	2,7	6	3
TC115-M4-C0-	TC115-M4-C0-	M 4	0,7	63	7	21	4,5	3,4	6	3
TC115-M5-C0-	TC115-M5-C0-	M 5	0,8	70	8	25	6	4,9	8	3
TC115-M6-C0-	TC115-M6-C0-	M 6	1	80	10	30	6	4,9	8	3
TC115-M8-C0-	TC115-M8-C0-	M 8	1,25	90	12	35	8	6,2	9	3
TC115-M10-C0-	TC115-M10-C0-	M 10	1,5	100	15	39	10	8	11	3

Příklad objednávky sorty WY80AA: TC115-M1.6-C0-WY80AA

DIN 376



Označení WY80AA	Označení WY80FC	DN	P mm	l ₁ mm	L _c mm	l ₃ mm	d ₁ h9 mm	□	l ₉ mm	N
TC115-M12-L0-	TC115-M12-L0-	M 12	1,75	110	16	83	9	7	10	3
TC115-M14-L0-	TC115-M14-L0-	M 14	2	110	20	81	11	9	12	3
TC115-M16-L0-	TC115-M16-L0-	M 16	2	110	20	68	12	9	12	3
TC115-M20-L0-	TC115-M20-L0-	M 20	2,5	140	25	95	16	12	15	4

Příklad objednávky sorty WY80AA: TC115-M12-L0-WY80AA

**WALTER
SELECT**

Optimální nástroj pro → dobré = 😊 → střední = 😐 → nepříznivé = ☹️ podmínky obrábění



● hlavní použití ● další použití

Strojní závitník HSS-E

TC115 Perform mm




– Pro materiály s dlouhou třískou



	P	M	K	N	S	H	O
WY80AA	●●	●●	●●	●			


DIN 371



Označení WY80AA	DN	P mm	l ₁ mm	L _c mm	l ₃ mm	d ₁ h9 mm	□	lg mm	N
TC115-M3-CE-	M 3	0,5	56	6	18	3,5	2,7	6	3
TC115-M4-CE-	M 4	0,7	63	7	21	4,5	3,4	6	3
TC115-M5-CE-	M 5	0,8	70	8	25	6	4,9	8	3
TC115-M6-CE-	M 6	1	80	10	30	6	4,9	8	3
TC115-M8-CE-	M 8	1,25	90	12	35	8	6,2	9	3
TC115-M10-CE-	M 10	1,5	100	15	39	10	8	11	3

Příklad objednávky sorty WY80AA: TC115-M10-CE-WY80AA

DIN 376



Označení WY80AA	DN	P mm	l ₁ mm	L _c mm	l ₃ mm	d ₁ h9 mm	□	lg mm	N
TC115-M12-LE-	M 12	1,75	110	16	83	9	7	10	3
TC115-M14-LE-	M 14	2	110	20	81	11	9	12	3
TC115-M16-LE-	M 16	2	110	20	68	12	9	12	3
TC115-M20-LE-	M 20	2,5	140	25	95	16	12	15	4

Příklad objednávky sorty WY80AA: TC115-M12-LE-WY80AA

**WALTER
SELECT**

Optimální nástroj pro → dobré = 😊 → střední = 😐 → nepříznivé = ☹️ podmínky obrábění

●● hlavní použití ● další použití